



BERING NUMBER		Dimensions (Inch)		Width			Radius r	Basic Load lbs	
8000	87000	ID d	OD D	B	B1	B2		Static Cr	Dynamic Cor
8500	87500	10	30	12.7	9	12.2	0.6	465	1047
8011	87011	11	32	12.7	10	12.2	0.6	626	1375
8501	87501	12	32	12.7	10	12.2	0.6	626	1375
8013	87013	13	32	12.7	11	12.2	0.6	626	1375
8014	87014	14	35	12.7	11	12.2	0.6	747	1525
8502	87502	15	35	12.7	11	12.2	0.6	747	1525
8016	87016	16	35	12.7	11	12.2	0.6	747	1525
8602	87602	15	42	15	13	14	1.0	976	1940
8503	87503	17	40	14.288	12	13.67	0.6	976	1940
8603	87604	17	47	16	14	15	1.0	1494	2885
8504	87504	20	47	15.875	14	15.24	1.0	1494	2885
8604	87604	20	52	19	15	18	1.0	1785	3150
8505	87505	25	52	15.875	15	15.24	1.0	1785	3150
8605	87605	25	62	21	17	21	1.0	1785	3150
8026	87026	26	52	15.875	15	15.24	1.0	1785	3150
8506	87606	30	62	20	16	19	1.0	1140	1970
8606	87606	30	72	23	19	23	1.0	1140	1970
8507	87507	35	72	21	17	20	1.0	1330	2120
8607	87607	35	80	25	21	25	1.5	1330	2120
8508	87508	40	80	24	21	24	1.0	1820	2960
8608	87608	40	90	27	23	27	1.5	1820	2960
8509	87509	45	85	24	21	24	1.0	2050	3300
8609	87609	45	100	30	25	30	1.5	2050	3300
8510	87510	50	90	26	22	26	1.0	2350	3560
8511	87511	55	100	27	23	27	1.5	2970	4390
8512	87512	60	110	29	25	29	1.5	3070	5900

8000 Series = Single seal one side only

Material: Chrome Steel SAE 52100

87000 Series = Sealed on both side, one side metal seal and the other rubber felt seal.

Other sizes are available upon request.